



## PREFERRED CLIMATE SOLUTIONS

No flame. No fumes. No fuss.

# TD625

### PERFORMANCE

- FUEL: DIESEL #2
- MAX BTU OUTPUT: 625,000
- EFFICIENCY: 92%+
- CFM: 4,500+
- STATIC PRESSURE: 3.5"
- TEMPERATURE: 180°F
- MAX FUEL CONSUMPTION: 4.9GPH

### POWER PLANT

- Kohler 2504 (74HP - No DEF)
- CAT 2.2L (74HP - No DEF)

### DIMENSIONS

- Weight, Full: Approx. 4,420 lbs
- Weight, Empty: 3,300 lbs
- Cabinet Height: 6'6"
- Overall Length: 12'4"
- Overall Width: 5'6"

### FUEL CAPACITY

- 200 GALS
- 150 GALS DOUBLE CONTAINMENT

### FEATURES

- Remote Site Thermostat Control
- Duct Storage
- Torsion Axle
- Double Fuel Containment - Optional



### CERTIFIED TO

UL733-2013 & CSA B 140.8.1967(R2015) STANDARDS  
REPORT NUMBER: 0489HH001S

Ideal for applications where an open flame or spark-risk is out of the question; the TD625 excels at providing 625,000 BTUs of clean, dry heat.

The patented technology uses a diesel power engine to agitate hydraulic oil in flameless, sparkless, low-pressure environment. In addition, an overspeed air intake shutoff valve is standard equipment. The oil is heated and circulated, not burned, providing a clean pollution free discharge to the target environment. Safety features are incorporated to protect the investment of your Thermo Dynamics heater.

All heaters are equipped with a set of four shut-off switches that terminate the engine when excessive pressures, speed or water temperatures are detected.

Preferred Climate Solutions  
Office: 888-466-7180

[www.preferredclimatesolutions.com](http://www.preferredclimatesolutions.com)

Dallas, Fort Worth, Houston, Austin, San Antonio & Oklahoma City



PREFERRED CLIMATE  
SOLUTIONS